



Valver Air Speed

VALVER spray guns.

Excellent finishes in
LARGE PRODUCTIONS.

threads available

- ref. **PIAE000073400**
1'2Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073401**
1'3Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073402**
1'4Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073403**
1'5Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073404**
1'6Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073405**
1'75Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073406**
2'2Ø VALVER VV-10 G gravity spray gun
- ref. **PIAE000073407**
2'8Ø VALVER VV-10 G gravity spray gun



wood



industry



car



gravity



VV-10 G

AIRBRUSH

HIGH SERIES

Qualities

- Wrought aluminum body and surface treated with a layer of green anodized.
- High hardness including threads.
- Teflon seals. Resistance to solvents.
- Fluid peak and needle are made of AISI 303 stainless steel.
- Independent axes in air valve and needle: easy to disassemble and lower maintenance.
- Polyamide drip Cup.
- Teflon valve peak needle: soft regulation without noise or friction.
- Products regulator spring with Teflon block: soft regulation without noise or friction with the spring.
- Fan, product and air pressure regulation.
- Easy handling, ergonomic design and light weight.
- Progressive fan regulation.

Features

Basic threads available (mm)	1,40
Recommended air working pressure (bar)	3-5
Aprox. air consumption (l/min)	300
BSP air inlet thread (G)	1/4"
Cup capacity (cc)	500
Recommended compressor (CV)	3
Gun+Cup weight (g)	692

Composition Box

- Mod. VV-10 G spray gun.
- Cleaning brush.
- Key maintenance.
- Female M16x1.5 thread polyamide 500 cc Cup.
- Filter.

Box dimensions

Dimensions (mm)	260 x 190 x 190
Box weight (kg)	1,1

Valver Air Speed

tel. +34 96 397 58 16
fax +34 96 397 58 15
VALENCIA - SPAIN
valver@valver.com
www.valver.com

Valver Air Speed

VALVER air tips and gun accessories.

AIR TIPS

ACCESORIES:

ANTIESTATIC GUN
SPECIAL NO-DUST BLOWN

HEATED HOSE
LOW AIR PRESSURE



BRASS

BRASS

BRASS

ALUMINIUM

ALUMINIUM

ALUMINIUM



HIGH SERIES MODEL VV-10 G GRAVITY SPRAY GUN

Hybrid Type: transfer approx: 65%

No. 4 -> from 1.00 to 1.75 mm holes, central Ø = 3mm

No. 5 -> 2.20 mm hole, central Ø = 3.7 mm

No. 6 -> 2.80 mm hole, central Ø = 4.6 mm

The air tips are the same, only central Ø varies

Excellent atomised

Hybrid Type: transfer approx: 65%

No. 20 -> from 1.20 to 1.40 mm holes,
central Ø = 3mm

Excellent atomised

Hybrid Type: transfer approx: 68%

No. 100 -> from 1.00 to 1.40 mm holes,
central Ø = 3.2mm

Excellent atomised

HVLP - approx transfer: 72%

No. 101 -> from 1.20 to 2.20 mm holes,
central Ø = 4.3mm

Seemly atomised

NOT VERY DEMANDING FINISHES.
BACKGROUND.

HOLE	AIR TIP	APPLICATIONS	METAL	FURNITURE	OTHERS
1,0-1,2	No. 4	VERY FINE FINISHES AND DYES		- DYES	- BOAT: POLYURETHANE FINISH
1,3	No. 4	FLUIDS PRODUCTS. VERY HIGH QUALITY FINISH		- DYES	
1,4-1,5	No. 4	HIGH QUALITY FINISH. PAINTED GENERAL	- ENAMEL	- VARNISH - PIGMENTED LACQUER	- PAINTINGS FOR PLASTICS
1,6	No. 4	HIGH SPEED APPLICATION	- ENAMEL - PRIMER	- VARNISH	- PAINTINGS FOR PLASTICS
1,75	No. 4	BIG SURFACES. PRIMER, BACKGROUND	- TEXTURIZED - PRIMER	- BACKGROUND AND PRIMER - SOLVENT BASED 2 K LACQUER	- BOAT: POLYURETHANE OR EPOXI PRIMER
2,2	No. 5		- FORGING TYPE		
2,5-2,8	No. 6	DENSE PRODUCTS	- FORGING TYPE	- FINISHES, BACKGROUND AND WATER BASED PRIMER	
1,2-1,3-1,4	No. 20	- VARNISH - HS ONE LAYERS			
1,0-1,2-1,3-1,4	No. 100	- WATER BASED 2 LAYERS BACKGROUND			

tel. +34 96 397 58 16
fax +34 96 397 58 15
VALENCIA - SPAIN
valver@valver.com
www.valver.com

